Product information presented here reflects conditions at time of publication. Consult factory regarding discrepancies or inconsistencies.



SECTION: 2.65.050 FM2801 0823 Supersedes 0222

TECHNICAL DATA SHEET

Drain Pump Series Model105


Remove water from areas where gravity flow is not available.

BASIN FEATURES

- Polypropylene construction
- 2" NPT vent
- 1-1/2" compression slip fit for top and side intake.
- Basin passes the 10' (3 m) stack test (models 104 and 132 will not)
- PVC "Full Flow" check valve with 1-1/2" or 1-1/4" slip X slip union (excludes model 104).
- · Threaded connections

MODEL 105

- 1/2" (12 mm) solids-passing capacity
- Temperature rated for 130°F (54°C)
- 1-1/2" NPT discharge
- 1550 RPM on 50 series pumps, 1725 RPM on 90 series
- M53, M55 and M98 with glass-filled polypropylene base
- M59 all bronze construction
- M57 and M63 all cast iron construction
- Includes 1-1/4" or 1-1/2" PVC slip x slip union check valve
- Passes laundry lint
- Automatic, float operated mechanical switch
- 9' (2.7 m), UL Listed, 3-wire cord and plug (15' [5 m] cord standard on model 98)
- Stainless steel screws, guard, handle and switch arm
- Non-clogging vortex impeller



* Models 104 & 132 are not UPC approved.










TOTAL DYNAMIC HEAD FLOW PER MINUTE




MODELS					/106 15/120			
Feet	Meters	Gal.	Liters	Gal.	Liters	Gal.	Liters	
5	1.5			43	163			
10	3.0			34	129			
15	4.6			19	72			
20	6.1							
Shut-off	Shut-off Head:				19.25 ft. (5.9m)		-	


009898

	Item No.	Model	MODEL COMPARISON											
			Seal	Mode	Volts	Discharge	Ph	Amps	НР	Cord (ft)	Hz	Lbs	Kg	Limited Warranty
	105-0001	105 (M53)	Single	Auto	115	1-1/2"	1	9.7	3/10	9'	60	30	14	36 months

INTERNAL TRAP ** Lavatory Sink




Wet Bar With Sink




** Trap provided by others

STANDARD INSTALL Laundry Tray Pump



Dehumidifier or Air Conditioner



Applications include: laundry tray pump, wet bar sink, lavatory, air conditioning condensate or dehumidifier water removal. It can also be used in conjunction with dishwashers and garbage disposal applications.